



Impact solutions for business and logistic environments

Compuprint 2056e



Compuprint 2056e satisfies typical needs in hospitals, hotels, retail stores, as well as in industrial and logistics environments. To these modern needs belongs the network capability which is available with 3 classic interfaces together in the standard model PRT2056EN. An entry model which serves the request for pure local connections like USB is available as well.

As a very economical printer the Compuprint 2056e helps to save money with its longlife ribbon of 10 million characters and its low power consumption.

Compuprint 2056e is the best choice for printing applications using multipart forms, single sheets, labels and envelopes.



Values and Features

- ✓ 24 pins print head (up to 500 Mio. strokes/pin)
- ✓ smart pin surveillance to substitute broken pins
- ✓ team player thanks to Ethernet 10/100 Base-T
- ✓ up to 4 interfaces in total: Ethernet, USB 2.0, parallel & serial
- ✓ great impact: 1 + 4 copies
- ✓ compact size: less than 39 cm width
- ✓ Workload: up to 10.000 pages a month

Versatile, economic and reliable

The Compuprint 2056e is most economic both in terms of its price and on duty. Print heads of impact printers are characterized by a high robustness and durability. Should it happen by any circumstances that a pin gets out of order, then the Compuprint 2056e can compensate it by its fast processor on board which allows to use other pins and to keep the throughput on a high level. Very high speed draft is good for up to 400 cps.



Compuprint 2056e – Your most economic network printer

Printer Model	PRT2056e
Print Technology	Serial Dot Matrix Printer
Printhead	24 pins (Ø 0,22 mm), Lifetime: 500 Mio strokes/pin
Print Speed	10 cpi: Very High Speed Draft 350 cps, High Speed Draft 283 cps, Draft 142 cps, LQ 94 cps
Print Width	Max. 80 columns @ 10 characters/inch
Paper Handling	+ Continuous Form: rear loading – paper width: 56 – 267 mm + Cut Sheet: paper width: 48 – 261 mm, weight: 52 – 90 g/m2 + Label: width of liner 101,6 – 254 mm, smallest label: 63.5 mm x 23.8 mm weight: max. 68 g/m2
Copies	1+ 4 – max. thickness: 0.52 mm
Special Functions	+ Automatic pin alternation (for decrease the workload on pins used most frequently) + smart pin surveillance to substitute broken pins + Printer configuration by remote control (PC-Software) or by browser in Ethernet-environment
Graphic Resolution	360 dpi x 360 dpi
Vertical Spacing	6 lines per inch; 8 lines per inch; n/360 per inch
Horizontal Spacing	10, 12, 15 cpi and proportional
1D-Codes (Barcodes)	EAN 8, EAN 13, 2/5 Interleaved, 2/5 Matrix, 2/5 Industrial, Code 39, Code 128, NW-7
Fonts	Draft, Courier, OCR-A, OCR-B, Prestige, Presentor, Roman, Sans Serif, Script
Character Sets	17 international character sets: U.S.A, France, Germany, U.K, Denmark 1 & 2, Sweden, Italy, Spain 1 & 2, Japan, Norway, Latin Am, Korea, Legal, Netherlands, Turkey IBM and EPSON character sets: CP 437 (USA), CP437G (Greek), CP850 (Multilingual), CP851 (Greek), CP852 (Eastern Europe), CP853 (Turkish), CP855 (Cyrillic), CP 861 (Island), CP863 (French-Canadian), CP860 (Portugal), CP865 (Danish-Norwegian), CP866 (Russian), CP1250 (Latin2 Windows), CP1252 (Latin1 Windows), CP1253 (Greek Windows), MAZOWIA, KAMENICKY, ISO Latin 1, 2, 7, 9, BULGARIA, HUNGARY, ARAB NLS, ARAB EXT, KBL
Emulations	Epson ® LQ ESC/P2, IBM ® Personal Printer 2391
Drivers	Windows 2000, XP, Vista, Win 7 - Win 10 (32 & 64 bit)
Interfaces	PRT2056E: USB 2.0 (Full Speed), Parallel IEEE1284 bidirectional PRT2056EN: Ethernet 10/100 Base-T, USB 2.0 (Full Speed), Parallel IEEE1284 bidirectional, serial RS232
Buffer	256 KB
Ribbon life	Black ribbon, up to 10 million characters in draft
Noise	< 53 dB (A) (ISO 7779 Standard)
Power Supply	Standard: 176 – 242 V, 50 Hz Option: 100 – 110 V, 60 Hz
Power Consumption	Printing: 50 W on average, Standby: 2,5 W
Dimensions	Depth: 28,0 cm, Width: 38,4 cm, Height: 13,9 cm
Weight	6 kg

Printer and Supplies

Compuprint 2056e with USB 2.0 and parallel I/F	PRT2056E
Compuprint 2056e with Ethernet, USB, par. & serial	PRT2056EN
Black ribbon, 10 million characters in draft	PRK2080-1

Compuprint

